

OWON CP024 AC/DC Oscilloscope Current Probe



- 4A to 400A test range
- Error by earth magnetic: $\pm 30\text{mA}$ max
- Remanence ($\pm 100\text{A}/10\text{A}$): $\pm 30\text{mA}$ max
- Bandwidth: DC 200KHz ($\pm 3\text{dB}$)
- Jaw size: 23mm (Max)
- Auto Zero at power on
- Low battery indication

TECHNICAL SPECIFICATION

DC Current

DC 4A, 1 mV/10 m A, $\pm(1.5\%\text{rdg}\pm 5\text{d})$

DC 40A, 1 mV/ 0.1A, $\pm(1.5\%\text{rdg}\pm 5\text{d})$

DC 300A, 1 mV/ 1A, $\pm(1.5\%\text{rdg}\pm 5\text{d})$

DC 300~400A, 1 mV/ 1A, $\pm(3.0\%\text{rdg}\pm 5\text{d})$

AC Current

AC 4A, 1 mV/ 10mA, $\pm(2.0\%rdg\pm5d)$

AC 40A, 1 mV/ 0.1A, $\pm(2.0\%rdg\pm5d)$

AC 300A, 1 mV/ 1A, $\pm(2.0\%rdg\pm5d)$

AC 300A~400A, 1 mV/ 1A, $\pm(3.0\%rdg\pm5d)$

General Specifications

Power supply: 9V (6LR61) Battery (Not included)

Dimension(W*H*D): 180 x 68 x 32 (mm)

Device Weight: About 250 g

Operating Temperature: 0°C to 50°C, $\leq 70\%RH$

Package Included:

1 x CP024

1 x Quick Guide

1 x Soft bag

1 x Manual

Warranty: 1 Year